

# QuickFix Mounting

## GUARANTEED ADHESION:

QuickFix is a self-adhesive unit with a bonding power which will bear a continuous load of 1.1 lb. The high-performance industrial grade adhesive strip is non-deteriorating and carries high safety tolerances.

## SIMPLE EN/DIN RAIL ATTACHMENT:

Mounting DIN Rail is made much easier by the borings in QuickFix. Longer rails are simply mounted on several QuickFix units. The connecting parts are just as easily positioned. Attach the DIN Rail with the screws provided. Guaranteed stable and twist proof.

## COST REDUCING:

QuickFix reduces labor and supply costs because it makes many time-consuming assembly steps unnecessary. For example, thermostats for enclosure heaters are fastened securely on side walls without the need for drilling holes and installing costly bolts.

## APPLICATION:

Direct attachment of small components and 35 mm DIN Rail.

## CAPACITY:

0.44 lb. (200g) initially, 1.1 lb. (500g) after 24 hour waiting period.

## MOUNTING SURFACE:

All smooth surfaces, E.G. metals, lacquered surfaces, plastics other than polyethylene, polypropylene and rubber. Mounting surfaces must be dry, free from dust, oil, separating agents and other contamination.

## DIMENSIONS:

1.7 X 1.5 X 0.55" (43 X 38 X 14 mm).

## HOLE PATTERN:

0.5" distance;  $\varnothing$  0.14" (12.8mm; 3.6mm).

## MATERIAL:

Polyamide (rated UL 94V-O) with non-deteriorating high-performance adhesive.

## TEMPERATURE RANGE:

-22° to 131°F (-30° to +55°C)

## PART # 09510.0-01

Includes 5 units per package with mounting screws for DIN Rail.

## EXAMPLES OF USE

