



**DIN RECEPTACLE**

DIN rail mounting power socket, with fuse  
6.3A/250V. Pressure clamp connections for easy  
and quick wiring  
UL/CSA Recognized component

**Technical Data**

Fuse Data	Ø 5 x 20mm, rated 6.3A
Mounting	Clip for 35mm DIN rail
Connection	3 x AWG 20-16 (0.5 - 1.5mm <sup>2</sup> )
Dimensions	3.6 x 2.4 x 1.9" (92 x 62 x 48mm)

Part Number		Operating Voltage
6.3A Fuse	No Fuse	
03504.0-00	03504.0-01	125 VAC



**DUAL SIDE GFCI RECEPTACLE**

Testing and resetting a GFCI inside an enclosure is impractical. Our **IN**side - **OUT**side is a practical and cost efficient solution.

Part No.	Description
H-RF0-K3-U400	NEMA 12, 4
H-RF15-K3-U400	NEMA 12, 4 with 15A CB
H-RF0-K2-U400	NEMA 4x
HRF-15-K2-U400	NEMA 4x with 15A CB



**INTERFACE RECEPTACLE**

Part No.	Description
P-XX-B3R0-U400	NEMA 12, 4
P-XX-B2R0-U400	NEMA 4x

**DOOR SWITCH**

To activate any electrical device. Cable entry PG 13.5  
Switching Load 6A-230V. UL-CSA approved.

Part No	ADSW-01
---------	---------